

Isopropyl Alcohol, SEMI+

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Isopropyl Alcohol, SEMI+

Synonyms/Generic Names: IPA, Isopropanol, 2-propanol, sec-Propyl alcohol

Product Number: 2884

Product Use: Industrial, Manufacturing or Laboratory use

Manufacturer: Columbus Chemical Industries, Inc.
N4335 Temkin Rd.
Columbus, WI. 53925

For More Information: 920-623-2140 (Monday-Friday 8:00-4:30)
www.columbuschemical.com

In Case of Emergency Call: CHEMTREC - 800-424-9300 or 703-527-3887 (24 Hours/Day, 7 Days/Week)

2. HAZARDS IDENTIFICATION

Hazard Not Otherwise Classified (HNOC): None

Target Organs: Nerves, Kidneys, Cardiovascular system, Gastrointestinal tract, Liver

Signal Word: Danger

Pictograms:



GHS Classification:

Flammable liquids	Category 2
Skin irritation	Category 3
Eye irritation	Category 2A
Specific target organ toxicity-single exposure	Category 3

GHS Label Elements, including precautionary statements:

Hazard Statements:

H225	Highly flammable liquid and vapor
H316	Causes mild skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Precautionary Statements:

P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/Bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray.
P264	Wash hands thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor/physician if you feel unwell.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P370+P378	In case of fire: Use appropriate media to extinguish.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local regulations.

Potential Health Effects

Eyes	Causes eye irritation.
Inhalation	May be harmful if inhaled. Causes respiratory tract irritation. Vapors may cause drowsiness and dizziness. Can cause irritation of mucous membranes and central nervous system depression.
Skin	May be harmful if absorbed through skin. Causes skin irritation.
Ingestion	May be harmful if swallowed.

NFPA Ratings

Health	1
Flammability	3
Reactivity	0
Specific hazard	Not Available

HMIS Ratings

Health	2
Fire	3
Reactivity	0

3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight %	CAS #	EINECS# / ELINCS#	Formula	Molecular Weight
Isopropyl Alcohol	>99	67-63-0	200-661-7	C ₃ H ₈ O	60.10 g/mol

4. FIRST-AID MEASURES

Eyes	Rinse with plenty of water for at least 15 minutes and seek medical attention.
Inhalation	Move casualty to fresh air and keep at rest. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.
Skin	Flush with plenty of water for at least 15 minutes while removing contaminated clothing and wash using soap. Get medical attention.

Ingestion	Do Not Induce Vomiting! Never give anything by mouth to an unconscious person. If conscious, wash out mouth with water. Get medical attention.
------------------	---

5. FIREFIGHTING MEASURES

Suitable (and unsuitable) extinguishing media	Flammable in the presence of a source of ignition when the temperature is above the flash point. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Use appropriate media for adjacent fire. Cool containers with water.
Special protective equipment and precautions for firefighters	Wear self-contained, approved breathing apparatus and full protective clothing, including eye protection and boots. Use water spray to cool fire-exposed containers and disperse vapors. Containers may rupture in the heat of the fire. Do not use direct water stream, may spread the fire.
Specific hazards arising from the chemical	Emits toxic fumes (carbon oxides) under fire conditions. Vapors can travel to a source of ignition and flash back. Containers may explode in a fire. Cool containers from a distance using water spray. Flames may be invisible. (See also Stability and Reactivity section)

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	See section 8 for recommendations on the use of personal protective equipment.
Environmental precautions	Do not let product enter drains. Any release to the environment may be subject to federal/national or local reporting requirements.
Methods and materials for containment and cleaning up	Absorb spill with vermiculite or other noncombustible absorbent material, then place in a suitable container for disposal. Clean surfaces thoroughly with water to remove residual contamination. Dispose of all waste and cleanup materials in accordance with local regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Use with adequate ventilation and grounding. Wash thoroughly after using. Keep container closed when not in use. See section 8 for recommendations on the use of personal protective equipment. Avoid contact with skin and eyes. Avoid inhalation of vapor or mist. Use explosion-proof equipment. Take measure to prevent the buildup of electrostatic charge.

Conditions for safe storage, including any incompatibilities

Store in tightly closed, original containers in a cool, dry, well ventilated area. Do not store with strong oxidizing agents, strong acids, peroxides, aldehydes, halogens, ammonia, acid anhydrides or alkali metals. Keep away from incompatible materials (see section 10 for incompatibilities).

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational exposure controls: Appropriate grounding of containers.

Component	Exposure Limits	Basis	Entity
Isopropyl Alcohol	200 ppm	TLV	ACGIH

	492 mg/m ³		
	400 ppm 984 mg/m ³	STEL	ACGIH
	400 ppm 980 mg/m ³	PEL	OSHA
	2000 ppm	IDLH	OSHA
	400 ppm 980 mg/m ³	REL	NIOSH
	500 ppm 1225 mg/m ³	STEL	NIOSH

TWA: Time Weighted Average over 8 hours of work.

TLV: Threshold Limit Value over 8 hours of work.

REL: Recommended Exposure Limit

PEL: Permissible Exposure Limit

STEL: Short Term Exposure Limit during x minutes.

IDLH: Immediately Dangerous to Life or Health

WEEL: Workplace Environmental Exposure Levels

CEIL: Ceiling

Personal Protection

Eyes	Wear chemical safety glasses or goggles, and face shield.
Inhalation	Provide local exhaust, preferably mechanical. If exposure levels are excessive, use an approved respirator.
Skin	Wear nitrile or rubber gloves, and full body covering. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
Other	Not Available

Other Recommendations

Provide eyewash stations, quick-drench showers and washing facilities accessible to areas of use and handling. Have supplies and equipment for neutralization and running water available.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance (physical state, color, etc.)	Clear, colorless liquid
Odor	Mild alcohol
Odor threshold	Not Available
pH	Not Available
Melting point/freezing point	-89°C (-129°F)
Initial boiling point and boiling range	82°C (180°F)
Flash point	12°C (54°F)
Evaporation rate	3.0
Flammability (solid, gas)	Flammable
Upper/lower flammability or explosive limit	LEL: 2.5% UEL:12%
Vapor pressure	33 mmHg (@ 20°C)
Vapor density	2.07 (air=1)
Relative density	Not Available
Solubility (ies)	Completely soluble in water
Partition coefficient: n-octanol/water	Log Pow: 0.05
Auto-ignition temperature	399°C (750°F)
Decomposition temperature	Not Available

10. STABILITY AND REACTIVITY

Chemical Stability	Stable
---------------------------	--------

Possibility of Hazardous Reactions	Will not occur.
Conditions to Avoid	Keep away from heat, flame and sparks
Incompatible Materials	Acids, alkali metals, oxidizing agents, iron salts, potassium, aluminum. May attack plastics and rubber.
Hazardous Decomposition Products	Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Skin	LD50 – rabbit – 18,286 mg/kg
Eyes	Not Available
Respiratory	Not Available
Ingestion	LD50 – mouse – 5,143 mg/kg

Carcinogenicity

IARC	3-Group 3: Not classifiable as to its carcinogenicity to humans (Isopropyl Alcohol).
ACGIH	A4: Not classifiable as a human carcinogen (Isopropyl Alcohol).
NTP	No components of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
OSHA	No components of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Signs & Symptoms of Exposure

Skin	Burning, itching, redness. May be harmful if absorbed through skin.
Eyes	Redness, excessive blinking and watering eyes.
Respiratory	Coughing, wheezing, headache, disorientation, blurred vision, dizziness, fatigue or nausea.
Ingestion	Nausea, vomiting and central nervous system depression.

Chronic Toxicity	May cause damage to the following organs: kidneys, liver, skin, central nervous system.
Teratogenicity	Not Available
Mutagenicity	Not Available
Embryotoxicity	Pre- and Post- implant mortality.
Target Organ(s)	May cause drowsiness or dizziness. Kidneys, Cardiovascular system, Gastrointestinal tract, Liver
Reproductive Toxicity	Not Available
Respiratory/Skin Sensitization	Not Available

12. ECOLOGICAL INFORMATION

Aquatic Vertebrate	Not Available
Aquatic Invertebrate	Not Available
Terrestrial	Not Available

Persistence and Degradability	Not Available
Bioaccumulative Potential	Not Available
Mobility in Soil	Not Available
PBT and vPvB Assessment	Not Available
Other Adverse Effects	Not Available

13. DISPOSAL CONSIDERATIONS

Waste Product or Residues	Users should review their operations in terms of the applicable federal/national or local regulations and consult with appropriate regulatory agencies if necessary before disposing of waste product or residue.
Product Containers	Users should review their operations in terms of the applicable federal/national or local regulations and consult with appropriate regulatory agencies if necessary before disposing of waste product container.

The information offered in section 13 is for the product as shipped. Use and/or alterations to the product may significantly change the characteristics of the material and alter the waste classification and proper disposal methods.

14. TRANSPORTATION INFORMATION

US DOT	UN1219, Isopropanol, 3, pg II
TDG	UN1219, ISOPROPANOL, 3, PG II
IMDG	UN1219, ISOPROPANOL, 3, PG II
Marine Pollutant	No
IATA/ICAO	UN1219, Isopropanol, 3, pg II

15. REGULATORY INFORMATION

TSCA Inventory Status	All ingredients are listed on the TSCA Active inventory.
DSL / NDSL	All ingredients are listed on the DSL inventory.
California Proposition 65	Not Listed
Rhode Island: Hazardous Substance List	Listed: Isopropyl Alcohol
Massachusetts: Toxic or Hazardous Substance List, Right to Know	Listed: Isopropyl Alcohol
Pennsylvania: Hazardous Substance List	Listed: Isopropyl Alcohol
New Jersey: Right to Know Hazardous Substance List	Listed: Isopropyl Alcohol
SARA 302	Not Listed
SARA 304	Not Listed
SARA 311	Fire Hazard, Acute Health Hazard, Chronic Health Hazard.
SARA 312	Fire Hazard, Acute Health Hazard, Chronic Health Hazard.
SARA 313	Listed: Isopropyl Alcohol (mfg-strong acid process).
WHMIS Canada	Class B2: Flammable and combustible material – Flammable liquid. Class D2B: Poisonous and infectious material – Other effects – Toxic.

16. OTHER INFORMATION

Revision	Date
Original	07/17/2018
Revision 1	02/28/2022

Disclaimer: The information provided in this Safety Data Sheet ("SDS") is correct to the best of our knowledge, information, and belief at the date of publication. The information in this SDS relates only to the specific Product identified under Section 1, and does not relate to its use in combination with other materials or products, or its use as to any particular process. Those handling, storing, or using the Product should satisfy themselves that they have current information regarding the particular way the Product is handled, stored or used and that the same is done in accordance with federal, state and local law. WE DO NOT MAKE ANY WARRANTY, EXPRESS OR IMPLIED, INCLUDING (WITHOUT LIMITATION) WARRANTIES WITH RESPECT TO THE COMPLETENESS OR CONTINUING ACCURACY OF THE INFORMATION CONTAINED HEREIN OR WITH RESPECT TO FITNESS FOR ANY PARTICULAR USE. WE DO NOT ASSUME RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR LOSS, INJURY, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH THE HANDLING, STORAGE, USE OR DISPOSAL OF THIS PRODUCT.